

Operating Instructions

1. Place on level ground in shaded area for best results.
2. Plug the units power cord in to standard household outlet (110 ACV) Note: Do not use more than a 50 foot extension cord because it may cause power failure.
3. Open top lid and gently lower Keg to bottom, centered in Barrel.
4. Connect supplied Taper to Keg. With tap handle in the up position, place tap in Keg connection and turn clockwise to lock tap to Keg Note: be sure hoses are free from kinking.
5. Lower taper handle on tap and that will pressurize hose and top tower. (Check for any leaks at the connection and tower handle this time) if leaks are present, pull up tap handle and repeat #4 and #5
6. Bleed off excess pressure of Keg by pulling pressure relief ring located on Keg taper.
7. Close lid and secure lid with latch (if equipped) . Note: As lid closes be sure not to kink any hoses
8. Turn on CO2 tank using top round valve on tank (Counter Clock wise) and position small valve handle in line with hose (Located at hose to tank connection) Note: do not adjust the pressure on Regulator more than 8 L/B
9. Pull Beer tower handle toward front to pour beer.
10. When finished using for the night, turn C02 tank off by turning round handle at top of tank (Clockwise)
11. When Keg is empty, unplug unit and turn C02 tank off by turning round handle at top of tank (Clockwise) to remove Keg follow instructions in reverse order.

Enjoy

For any instructions or problems, Call Mark at (310) 901-2043.

Acknowledgement of receiving.

Signature: